

Model	Go-Go® LX with CTS ¹
Part Number	3-wheel: S50LX 4-wheel: S54LX
Weight Capacity	300 lbs.
Maximum Speed ²	Up to 4.4 mph
Ground Clearance ⁴	1.5" at motor / 0.75" at anti-tips
Turning Radius ⁴	3-wheel: 33.5" 4-wheel: 44.75"
Overall Length ⁴	3-wheel: 39.75" 4-wheel: 41.75"
Overall Width ⁴	20.5"
Seat-to-Deck Height	16.25" - 17.75"
Seat-to-Ground Height	20.75" - 22.25"
Front Tires	3-wheel: 2" x 8" solid 4-wheel: 2" x 7" solid
Rear Tires	2.5" x 8" solid
Range Per Charge ^{2,3}	3-wheel: Up to 6 miles (12 AH) 4-wheel: Up to 5.5 miles (12 AH)
Total Weight Without Batteries	3-wheel: 85 lbs. 4-wheel: 90 lbs.
Heaviest Piece When Disassembled ⁴	3-wheel: 33 lbs. (front section) 4-wheel: 39 lbs. (front section)
Standard Seating	Type: Compact, foldable Weight: 23 lbs. Material: Black vinyl Width: 17", Depth: 17"
Motor Output	24-volt DC motor, sealed transaxle
Brakes	Regenerative and electromechanical
Battery Requirements ⁵	Size: (2) 12 AH Weight: 9 lbs. each, 20lbs.
Battery Charger	Off-board, 2 amp (12 AH)

HCPCS Code: K0899

POWER MOBILITY DEVICE, NOT CODED
BY DME PDAC OR DOES NOT MEET CRITERIA

- ¹ Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.
- ² Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
- ³ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- ⁴ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- ⁵ Battery weight may vary based on manufacturer.

PRIDE®
MOBILITY
LIVE YOUR BEST®

(US) 800-800-8586 • (Canada) 888-570-1113

pridemobility.com |    

HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.

0003145_061421

GO GO®¹
LX WITH CTS SUSPENSION

**THE
SMOOTHEST
RIDE IN TRAVEL
MOBILITY**



FDA Class II Medical Device¹

LIVE YOUR BEST®

pridemobility.com |    

THE SMOOTHEST RIDE IN TRAVEL MOBILITY




The Go-Go® LX with Comfort-Trac Suspension (CTS) offers a whole new level of comfort and performance. This industry-first CTS technology incorporates advanced suspension for improved absorption over various terrains. The Go-Go LX with CTS offers a 300 lb. weight capacity, a per charge range up to 8.6 miles and a maximum speed of 4.4 mph.

Additional Features

- Delta tiller with charger port for conveniently charging your scooter
- Convenient dual voltage charger can charge battery pack on-board or off-board
- Includes two sets of easily changeable, red and blue colored panels
- Long-lasting, high-intensity, front LED headlight offers optimal pathway illumination
- Microprocessor-based controller offers optimal power management and added safety features

Colors



Accessories*

- Cane clip attachment
- Cane/crutch holders
- Cell phone holder
- Cup holder
- 50" Lap belt
- Oxygen tank holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Under seat storage
- Walker holder
- Weather cover
- XLR USB charger
- Additional 12AH battery

Military Patches



* Only one rear accessory can be used at a time.



Charger port located conveniently in tiller.



Feather-touch disassembly for quick transport or storage.



Comfort-Trac front and rear suspension for added comfort.